



PROPERTY INFO				
and the Target	SQFT	ACRES		
PROPERTY	193,677	4.45		
BUILDING AREA	4,830	0.11		
IMPERVIOUS AREA(LESS BLDG.)	149,695	3.44		
LANDSCAPE AREA	39,152 (20.20%)	0.90		
SETBACKS	BUILDING			
FRONT	N/A	4 2 1 2		
REAR	20' (WITHOUT ALLEY)			
SIDE	0'-0"	1 1 1 1		

PARKING RATIO					
	REQUIRED	PROVIDED			
TANDARD PARKING	N/A				
CCESSIBLE PARKING	N/A	14, 45			
VENTORY STORAGE	N/A	100			
OTAL		100			



LOCATION Map

Know what's below. Call before you dig.



NOTE: SEE AICHTECTURAL PLANS FOR EXACT LOCATIONS AND DIMENSIONS OF PORCHES, RAMPS, VESTIBLUE, SLOPED PAVING, TRUCK DOCKS, BUILDING LITELTY ENTRANCE LOCATIONS AND PRECISE BUILDING DIMENSIONS.

SITE BM81- N1488728.8765,E2186130.5310- ELEV= 887.79 SITE BM82- N1488478.3515,E2186093.1128- ELEV= 887.43 SITE BM83- N1488318.8975,E2186133.4278- ELEV= 889.18

LEGEND

H					
	FIRE HYDRANT	IR(N)	IRON ROD NEW	5500	CATCH BASIN (Size Varies-See Plan
500	WATER VALVE	IR(O)	IRON ROD OLD	(G)	GAS VALVE
(6" - 8" RED MAPLE	IP(O)	IRON PIPE OLD	[5]	GAS METER
400	and the grant manners	IP(N) SPK	IRON PIPE NEW	P	
56	10" - 12" WILLOW OAK	FN	SPIKE FENCE		FLAGPOLE
W	WATER	CMP	CORRUGATED METAL PIPE	-	GUY WIRE
040		(1)	STORM MANHOLE		CLEANOLIT
-GAS	GAS	8	SANITARY MANHOLE	-	CLEARODI
- OH	OVERHEAD WIRE	Bad	WATER METER		
- X	FENCE		POWER POLE		
- 55	SANITARY SEWER	.00	LIGHT POLE		

PROPOSED

PROPERTY LINE/RIGHT OF WAY LINE CONCRETE CURB AND GUTTER



PROPOSED PARKING SPACES

LIMITS OF SIDEWALKS AND CONCRETE APRONS (PER ARCH, PLANS)

GENERAL SITE NOTES

- A. ALL DIMENSIONS SHOWN ARE TO THE FACE OF CURB UNLESS OTHERWISE NOTED.
- B. ALL CURB RETURN RADII SHALL BE 2' OR 10', AS SHOWN TYPICAL ON THIS PLAN, UNLESS OTHERWISE NOTED.
- C. UNLESS OTHERWISE SHOWN, CALLED OUT OR SPECIFIED HEREON OR WITHIN THE SPECIFICATIONS: ALL CURB AND GUTTER ADJACENT TO ASPHALT PANING SHALL BE INSTALLED PER DETAIL OLD, PAVEMENT SHALL BE INSTALLED IN ACCORDANCE WITH DETAIL GOAR OVER THE ENTIRE PARKING LOT AREA AND ALL APPRIOCH DRIVES, ALL PARKING LO STRIPING INCLUDING ACCESSIBLE AND VAN ACCESSIBLE PAVES SHALL BE PAINTED PER DETAIL COUL.

SITE NOTES

- 180 MATCH EXISTING PAVEMENT ELEVATIONS.
 21.4 TAPER CURB TO MATCH EXISTING CURB.
 70.4 ASPHALT PAVEMENT TO MATCH EXISTING.
 70.8 REUSE PORTION OF DEMOUSHED FENCE TO CONNECT TO EXISTING FENCE.

☐ SITE DETAILS

- OIA TYPE A CONCRETE CURB AND GUTTER
 GISK. CONCRETES SIDEWALK.
 GIVEN WHEELCHAIR RAMP IN SIDEWALK (TYPICAL AT EACH DRIVEWAY CURB RETURN)
 GICL THICKENED EDGE OF PAVING
 70 A. 7 AMERIA TAC COMMERCIAL MONTAGE CLASSIC STYLE 3 RAIL FENCE (OR APPROVED
- EQUAL)

 708 TRANSPORT II SLIDING CANTILEVER GATE CLASSIC STYLE (OR APPROVED EQUAL)

RECEIVED AUG 0 4 2017

